

Tomcat Carbon Scrubber (Large)

Before use:

Put water in the machine: You can fill it up 1 of 2 ways. Under the black flap in the front is a fill tube that you can hook to faucet, or you can put the hose in the mesh screen. There is a sight indicator on the left rear of machine (Clear tube)

Put soap in the machine: Follow directions on the back of detergent of your choice. Do not put too much in as it can cause excess foam to get into the vac motor.

Make sure that pads, or brushes are installed on the scrubber. Located at the front of the machine behind the front shroud.

Operation:

Turn the key to the on position.

Turn on the brush switch: Located on the control panel, you can also adjust down pressure, and water output with the toggle switches on the control panel.

Drop Squeegee: The top of machine by the control panel is a lever, slide that to the right and it will lower the squeegee. (reverse this to bring it back up)

Adjust the water output: There is a blue toggle switch on the control panel; push up and down to control the flow.

Set your speed: On the control panel is a red dial (potentiometer). Turn that to your desired speed, you can also adjust as you are scrubbing.

Reverse: The reverse is under the left-hand grip. To reverse pull back with index finger, while gripping the buttons on the handle.

Let's get scrubbing: To propel forward grip the buttons on the handle.

After use:

Drain the Recovery Tank: The dirty water drain is located on the right rear of machine. Remove cap and put end of hose on your floor drain, etc.

Drain the Solution Tank: The solution tank drain is on the left rear of the machine. Just take the hose and pull it off the upper barb and put on the floor drain.

Clean Machine: Wipe down the exterior. Drain and rinse the recovery tank.

Thank you for renting from Bell Janitorial Supply, we look forward to renting to you again!!